# Biodegradable Nonvolatile Memory Composed of Almost Nanocellulose

Kazuki Nagashima<sup>1</sup>, Umberto Celano<sup>2</sup>, Hirotaka Koga<sup>3</sup>, Masaya Nogi<sup>3</sup>, Jo De Boeck<sup>2</sup>, Malgorzata Jurczak<sup>2</sup>, Wilfried Vandervorstand<sup>2</sup> and Takeshi Yanagida<sup>1,3</sup>

IMCE Kyushu Univ.<sup>1</sup>, imec<sup>2</sup>, ISIR Osaka Univ.<sup>3</sup>

Discarding the electronic instruments is a serious social issue, since the materials used in electronic devices are not biodegradable, not renewable and sometimes toxic to the environment and the living beings. One idea to overcome this issue is the development of electronic devices composed of biodegradable, renewable, environmentally safe materials, however, in general such materials are mechanically and thermally fragile and therefore it has been difficult to realize the robust electronic properties. In this study, we demonstrate the biodegradable nonvolatile memory composed of almost nanocellulose. Nanocellulose is most abundant biomass on earth and its excellent mechanical and thermal stability has been recently reported. The device consists of nanocellulose substrate, nanocellulose film memory [1] and electrodes, and is 99.3 vol.% composed of nanocellulose. The device showed the robust memory properties and the good scalability down to single nanocellulose scale (~15nm). At the end of use, the electrode materials could be separated in water by simply applying the sonication. Furthermore, the device was fully biodegradable within 30 days in the natural soil. Thus, our findings open the platform for environmental friendly green electronics using biodegradable nanocellulose.

[1] K. Nagashima et al. Sci. Rep. 4, 5532 (2014)

# **Biodegradable Nonvolatile Memory Composed of Almost Nanocellulose**



K. Nagashima<sup>1</sup>, U. Celano<sup>2</sup>, H. Koga<sup>3</sup>, M. Nogi<sup>3</sup>, J. D. Boeck<sup>2</sup>, M. Jurczak<sup>2</sup>, W. Vandervorstand<sup>2</sup>, T. Yanagida<sup>1,3</sup>

<sup>1</sup>IMCE Kyushu Univ. <sup>2</sup>imec <sup>3</sup>ISIR Osaka Univ.

## **Background**



3.2 million tons of electronic waste per year in US

### Paper electronics ~toward sustainable electronics~

Cellulose nanofiber paper (CNP)

-Biodegradable






What is an alternative way for sustainable electronics?

### Can we demonstrate the eco-cycle compatible nonvolatile memory device?

# **Experimental**



Atomic force microscopy

(tapping mode & contact mode) ductor parameter analyzer

y4200SCS, air, room temperature) Ag: +/- ,ITO: GND, current compliance 50µA-1mA





at 34:49:30 north latitude 135:31:28 east longitu Temperature 22±2°C Humidity 92±3%

Plastic bag

### **Results and Discussions**

99.3% volume fraction of cellulose in paper memory






Clear nonvolatile memory property in paper memory


# Potential scalability of paper memory





Paper memory works down to a sing cellulose nanofiber scale

### Material sorting for recycle









Electrodes can be sorted by simply applying the sonication in polar solution

# Biodegradability

Paper memory showed high biodegradability into natural soil

### Summary

- •Paper memory with 99.3 % volume fraction of cellulose was demonstrated for the first time.
- •Paper memory is recyclable with low energy process and biodegradable into natural soil.

References [1] Nagashima et al. Sci. Rep. 4, 5532 (2014) [2] Celano et al in preparation